

Smart dosing system for swimming pools and spas

MAIN CHARACTERISTICS

The box is equipped with:

Peristaltic pump

- Nb : 1 or 2 according to the model
- Flow Rate : 1,5 L/H
- Pressure : 200 kPA (30 psi)

HMI backlighted 2 lines

Interface retro enlightened 2 lines with keyboard french and english software

- Voltage: 110 ou 240 VAC 50/60Hz
- Power : 20 W
- Cord : 1 m
- Box : Fiberglass Nema 4 IP54
- Size of the box : 10''x 8'' x 4'' (600 x 400 x 210 mm)
- Weight : 6.6 lbs (3 kg)
- Switch on/ off

Accessories included with the box:

- Tubing 4/6 mm for aspiration
- Tubing 4/6 mm for repression
- Saddle DN 1,5''ou 2''
- Injector 3/8''
- Suction strainer



Model	Length	Width	Height	Voltage- Power	Nb of pump (s)
947 9101	300 mm	250 mm	165 mm	120 volts 50-60 Hz-20W	1
947 9102	300 mm	250 mm	165 mm	120 volts 50-60 Hz-20W	2
947 9121	300 mm	250 mm	165 mm	240 volts 50-60 Hz-20W	1
947 9122	300 mm	250 mm	165 mm	240 volts 50-60 Hz-20W	2

This box of proportioning is particularly adapted for the disinfection of the swimming pools, hot tubs, spas. It makes it possible to dispense two products, such as one sanitizer liquid and anti algae for example. It also makes it possible to ensure in time, of the processing of shock treatment. The entered data are protected, in the event of switch down.

The pumps are peristaltic type. The box is provided with a backlighted interface with 2 lines of liquid crystal. The pull-down menu is simple and makes it possible to program:

- A daily dosing in ml and to fix dispensing time
- Adosing time scheduled per day and incremented new dosing, with an adjustable interval of days.

The box allows a fickleness in proportionings and meets perfectly the variable need for disinfection for the aquatic basins.

